



# MEHR FLEXIBILITÄT DANK VERBESSERTER FUNKTIONEN

3-Zoll-POS-Bondrucker  
**SRP-350III**



## WESENTLICHE MERKMALE



### Ausgezeichnete Druckeigenschaften

- schnelles Drucken mit bis zu 250 mm/ Sekunde (25 % schneller als der SRP-350II)
- 4 Dithering-Optionen für Grafikdruck
- aus der Familie der erstklassigen SRP-350-Reihe



### Mehrere Schnittstellenoptionen

- USB integriert
- Optional: seriell, parallel oder Ethernet

### Benutzerfreundliches Design

- Anti-Papierstau-Führung
- Einzelplatzinstallation oder platzsparende Wandmontage
- Wahl zwischen 2- oder 3-Zoll-Papier



**BIXOLON**<sup>®</sup>  
a Better Solution for your Business<sup>™</sup>

# 3-Zoll-POS-Bondrucker SRP-350III



## TECHNISCHE DATEN

### Print Characteristics

**Print Method**

Direct Thermal

**Print Speed**

SRP-350III: 250 mm/sec

SRP-352III: 250 mm/sec

**Print Resolution**

SRP-350III: 180 dpi

SRP-352III: 203 dpi

**Print Width**

Up to 72 mm

**Sensor**

Paper End, Paper Near End, Cover Open

### Media Characteristics

**Media Type**

Receipt

**Media Width**

80 mm / 58 mm

**Media Roll Diameter**

Up to 83 mm

**Media Thickness**

0.062 ~ 0.075 mm

**Supply Method**

Easy Paper Loading

### Physical Characteristics

**Dimensions (WxLxD)**

145 x 204 x 146 mm

(5.70 x 8.03 x 5.74 inch)

**Weight**

1.55kg (3.41 lbs)

**Power**

EnergyStar Certified,

External Power Adaptor 100-240V AV, 50/60Hz

**Drawer Port**

2 ports (via y-type adaptor)

### Performance Characteristics

**Memory**

64 Mbit SDRAM, 32 Mbit FlashROM

**NV Image Memory**

256 Kbytes (mono)

**Receive Buffer**

4 Kbytes

**User Define Buffer**

12 Kbytes

**Interface**

Dual Interface

USB V2.0 FS + Serial

USB V2.0 FS + Parallel

USB V2.0 FS + Ethernet

### Environment Characteristics

**Temperature**

Operating: 0 ~ 45°C (32 ~ 113°F)

Storage: -20 ~ 60°C (-4 ~ 140°F)

**Humidity**

Operating: 10 ~ 80% RH

Storage: 10 ~ 90% RH

### Reliability

**Printer Unit (MCBF)**

70 Million Lines

**Thermal Print Head (TPH)**

150 km

**Auto Cutter**

1.8 Million Cuts

### Software

**Emulation**

BXL / POS

**Driver / Utility**

Windows Driver, OPOS Driver, JPOS Driver,  
Linux CUPS Driver, Mac Driver, Virtual COM USB/  
Ethernet Driver, Utility Program

**SDK**

iOS SDK, Android SDK

### Fonts / Graphics / Symbologies

**Character Size**

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24

KOR, CHN, JPN: 24 x 24

**Characters Per Line**

SRP-350III: Font A: 42 Font B, C: 56

KOR, CHN, JPN: 21

SRP-352III: Font A: 48 Font B, C: 64

KOR, CHN, JPN: 24

**Character Sets**

Alphanumeric: 95

Extended Graphics: 128 x 37 page

International: 32

**Graphics**

Supporting user-defined fonts, graphics, formats,  
and logos

**Barcode Symbologies**

1D: Codabar, Code 39, Code 93, Code 128,  
EAN-8, EAN-13, ITF, UPC-A, UPC-E

2D: Data Matrix, PDF417, QR code

BR-SRP-350III-DE-APR14

Copyright © BIXOLON Co., Ltd. All rights reserved.

Features and specifications are subject to change without prior notice.

# BIXOLON®

www.bixolon.com

**BIXOLON Co., Ltd.**

7~8F, (Sampyeong-dong), 20, Pangyoyeok-ro241beon-gil,  
Bundang-gu, Seongnam-si, Gyeonggi-do, 463-400, Korea (ROK)

Tel +82 (0) 31 218 5500

Fax +82 (0) 31 218 5589

E-mail sales@bixolon.com

**BIXOLON America Inc.**

3171 Fujita St Torrance,  
CA 90505, USA

Tel +1 858 764 4580

Fax +1 310 257 6869

E-mail sales@bixolonusa.com

**BIXOLON Europe GmbH**

Tiefenbroicher Weg 35,  
40472 Düsseldorf, Germany

Tel +49 211 68 78 54 0

Fax +49 211 68 78 54 20

E-mail sales@bixolon.de